

Engine Management System

VW SIMOS 18.5

EA888 (SCF)

Specification

Customer: Audi
Software Version: SCFN00Y0
Date: 2014-07-17
Document Key: 10265183 SPE 000 AE

Specification to customer

Diese Information ist lediglich eine technische Beschreibung des Produktes. Sie stellt keine Beschaffenheits- oder Haltbarkeitsgarantie im Sinne des Paragraphen 443 BGB dar.

This information is exclusively a technical description of the products. It is not meant or intends to be a special guarantee for a particular quality or durability with regard to section 443 BGB (German Civil Code).

Project: VW SIMOS 18.5 EA888 (SCF)

Customer: Audi

	Name	Department	Phone	Date	Sign
Designed by	Schneider, Michaela	P ES SYS I GER 12	+49-941-790-8384	2014-07-17	
Released by	Schneider, Michaela	P ES SYS I GER 12	+49-941-790-8384	2014-07-17	

Transmittal, reproduction, dissemination and/or editing of this document as well as utilisation of its contents and communication thereof to others without expressed authorisation are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.


Released by Schneider, Michaela		Date 2014-07-17	File SCFN00Y0
	Baseline SCFN00Y0	Project VW SIMOS 18.5 EA888 (SCF)	
	Document key 10265183 SPE 000 AE	Pages Page 1 of 25091	
Regensburg ()		Copyright (C) Continental AG, 2007	
		A4: 2007-11	

Table of Contents

1	Introduction	1086
1.1	System overview	1087
1.2	PIN configuration of connector	1093
1.3	Build Parameter	1107
1.4	Standard analog inputs	1109
1.5	Definition of logic inputs	1111
2	AIRM-Air motion	1112
2.1	AIRM Configuration data	1113
2.2	Port flap variables	1114
2.3	Port flap position set point actuation signal processing	1121
2.4	Port flap adaptation	1134
2.5	Port flap actuator diagnosis	1140
2.6	Port flap power stage diagnosis	1171
2.7	Port flap power stage diagnosis (Appl. Inc.)	1175
3	AIRT-Air temperature	1177
3.1	AIRT General	1178
3.2	AIRT Configuration data	1181
3.3	AGGR adaptation: AIRT	1188
3.4	Acquisition of air temperatures	1192
3.5	Acquisition of air temperatures (Appl. Inc.)	1195
3.6	Air temperature sensor model (Appl. Inc.)	1199
3.7	Air temperature sensor model	1201
3.8	Ambient air temperature calculation (Appl. Inc.)	1217
3.9	Ambient air temperature calculation	1222
3.10	Intake gas temperature calculation	1242
3.11	Intake gas temperature model at intake manifold	1248

3.12	Intake gas temperature model at intake valve	1259
3.13	Intake gas temperature model at throttle	1267
3.14	Intake gas temperature model at intercooler	1272
3.15	Intake gas temperature model for exhaust gas recirculation	1274
3.16	Intercooler air temperature control	1277
3.17	Signal diagnosis of temperatures delivered by INTC	1278
3.18	Air temperature sensor diagnosis (Appl. Inc.)	1285
3.19	Air temperature sensor diagnosis	1289
3.20	Air temperature sensor diagnosis (ERRM interface)	1296
3.21	Air temperature sensor plausibility diagnosis (Appl. Inc.)	1301
3.22	Air temperature sensor plausibility diagnosis	1304
3.23	Air temperature sensor plausibility diagnosis (ERRM interface)	1313
3.24	Intake gas temperature sensor plausibility diagnosis (Appl. Inc.)	1315
3.25	Intake gas temperature sensor plausibility diagnosis	1318
3.26	Intake gas temperature sensor plausibility diagnosis (ERRM interface)	1330

4	ALFU-Alternative fuel	1332
4.1	ALFU General	1333
4.2	ALFU Configuration data	1336
4.3	Ethanol sensor acquisition	1338
4.4	Engine roughness signal preparation for fuel quality adaptation	1347
4.5	Injection time correction for alternative fuel	1358
4.6	Engine running adaptation (AFU)	1360
4.7	Engine running adaptation (AFU) (Appl. Inc.)	1385
4.8	Lambda based flex fuel ratio detection	1387
4.9	Lambda based flex fuel ratio detection (Appl. Inc.)	1403
4.10	Fuel tank level based flex fuel ratio detection	1406
4.11	Fuel tank level based flex fuel ratio detection (Appl. Inc.)	1425
4.12	Engine roughness based flex fuel ratio detection	1430
4.13	Alternative fuel ratio determination	1431
4.14	Alternative fuel ratio determination (Appl. Inc.)	1438

4.15	Default start strategy	1457
4.16	Engine roughness based fuel quality adaptation	1477
4.17	Ethanol sensor diagnosis	1494
4.18	Ethanol sensor plausibility diagnosis	1497
4.19	ALFU - Controller (gen)	1503
4.20	ALFU - Controller (prj)	1509

5 ARSD-Acquisition and Reporting of Statistical Data 1510

5.1	Cyclic redundancy check calculation algorithm	1511
5.2	ARSD Configuration data for Customer Statistics	1514
5.3	Data recorder	1517
5.4	Customer statistical data	1538
5.5	Customer statistical data (Appl. Inc.)	1565
5.6	Standard data for OBD radar	1577

6 BRSY-Braking system 1590

6.1	BRSY Configuration data	1591
6.2	BRSY General	1593
6.3	Brake servo unit pressure	1598
6.4	Brake servo unit pressure (Appl. Inc.)	1622
6.5	Vehicle stand still detection	1630
6.6	Brake servo unit output	1639
6.7	Brake servo unit pump control	1645
6.8	Brake servo unit pressure sensor diagnosis	1653
6.9	Brake servo unit pressure sensor diagnosis (Appl. Inc.)	1673
6.10	Brake servo unit pump diagnosis	1676
6.11	Brake servo unit pump diagnosis (Appl. Inc.)	1687

7 CBMD-Combustion modes 1688

7.1	CBMD General	1689
7.2	CBMD Configuration data	1692

7.3	Combustion mode switch	1715
7.4	Combustion mode inhibition (Appl. Inc.)	1719
7.5	Combustion mode inhibition	1751
7.6	Combustion state manager	1759
7.7	Combustion state manager (Appl. Inc.)	1768
7.8	Combustion mode prioritisation	1783
7.9	Combustion mode request	1800
7.10	Combustion mode transition factors	1811
7.11	Combustion mode inhibition by minimum injection time (Appl. Inc.)	1815
7.12	Combustion mode inhibition by minimum injection time	1823
7.13	Combustion mode inhibition for scavenging	1847
7.14	Combustion mode summary	1857
7.15	Combustion mode request by operating point (Appl. Inc.)	1864
7.16	Combustion mode request by operating point	1881
7.17	Combustion mode request summary	1894
7.18	Combustion mode switch by diagnosis tool	1896
7.19	Combustion mode switch by diagnosis tool (error management interface)	1902
7.20	Combustion mode management (gen)	1904


8 CEVC-Crankcase evaporation control 1909

8.1	CEVC Configuration data	1910
8.2	AGGR adaptation: CEVC	1912
8.3	Oil dilution model	1916
8.4	Evaporation risk management	1954
8.5	Fuel evaporation model in crankcase	1984
8.6	Limitation of fuel correction from crankcase evaporation	2004
8.7	Evaporation risk management (ERRM interface)	2012

9 CHRA-Charger actuators 2017

9.1	CHRA Configuration data	2018
9.2	CHRA General	2021

9.3	Acquisition of pressure at pneumatic waste gate actuator	2026
9.4	Waste gate actuator pressure	2027
9.5	Recirculation actuator position	2033
9.6	Recirculation actuator position (Appl. Inc.)	2036
9.7	Recirculation actuator position control	2038
9.8	Turbocharger turbine actuator coordination	2040
9.9	Boost pressure actuator control diagnosis	2048
9.10	Recirculation actuator diagnosis	2056
9.11	Recirculation actuator diagnosis (Appl. Inc.)	2083
9.12	Waste gate electrical diagnosis	2085
9.13	Waste gate electrical diagnosis (Appl. Inc.)	2114
9.14	CHRA adaptation and diagnosis	2117
9.15	CHRA fault operation manager	2191
9.16	CHRA fault operation manager (Appl. Inc.)	2194
9.17	CHRA power stage diagnosis	2196
9.18	CHRA sensor diagnosis	2230
9.19	CHRA actuator diagnosis	2238
9.20	CHRA actuator diagnosis (Appl. Inc.)	2270
9.21	CHRA adaptation and diagnosis (Appl. Inc.)	2277
9.22	CHRA sensor diagnosis (Appl. Inc.)	2280
9.23	Boost pressure actuator diagnosis EOL	2281
9.24	CHRA diagnosis (gen)	2286
9.25	CHRA position control and setpoint (gen)	2292
9.26	Boost pressure actuator anti sticking	2309
9.27	Boost pressure actuator operating manager	2331
9.28	CHRA position controller	2359
9.29	Boost pressure actuator safety limitation	2376
9.30	CHRA safety limitation (Appl. Inc.)	2402
9.31	CHRA sensor acquisition	2404
9.32	CHRA cleaning	2411
9.33	Actuator temperature model	2415

Released by Schneider, Michaela		Date 2014-07-17	File N/A
	Baseline SCFN00Y0	Project VW SIMOS 18.5 EA888 (SCF)	
	Document key 10265183 SPE 000 AE	Pages Page 6 of 25091	
Regensburg ()		Copyright (C) Continental AG, 2007	A4: 2007-11


10	CHRG-Charger	2439
10.1	CHRG Configuration data	2440
10.2	Charge air temperature	2449
10.3	Recirculation mass air flow determination	2461
10.4	Exhaust gas temperature for turbocharger	2464
10.5	Turbocharger compressor environment	2466
10.6	Basic boost pressure adaptation (Appl. Inc.)	2472
10.7	Basic boost pressure	2474
10.8	Basic boost pressure adaptation	2479
10.9	Turbocharger compressor model	2484
10.10	Detection of compressor surge	2492
10.11	Boost pressure limits	2496
10.12	CHRG dummy outputs	2502
10.13	Pressure upstream throttle setpoint	2510
10.14	Pressure upstream throttle setpoint (Appl. Inc.)	2521
10.15	Turbocharger compressor environment setpoints	2528
10.16	Turbocharger protection	2532
10.17	Turbocharger protection (Appl. Inc.)	2537
10.18	Recirculation actuator setpoint determination	2539
10.19	Recirculation actuator setpoint determination (Appl. Inc.)	2557
10.20	Boost pressure control	2559
10.21	Boost pressure control (Appl. Inc.)	2568
10.22	Turbocharger turbine control adaptation	2577
10.23	Waste gate flow setpoint	2584
10.24	Turbocharger turbine control	2587
10.25	Turbocharger turbine control (Appl. Inc.)	2602
10.26	Inverse turbocharger turbine model	2613
10.27	Torque based charge air temperature limitation	2622
10.28	Torque based turbocharger speed limitation	2633
10.29	Turbocharger minimum time control	2645
10.30	Boost pressure display (Appl. Inc.)	2660

10.31	Boost pressure display	2664
10.32	Turbocharger diagnosis	2670
10.33	Turbocharger control plausibility diagnosis	2690
10.34	Turbocharger control plausibility diagnosis (ERRM interface)	2702
10.35	Turbocharger overpressure diagnosis (Appl. Incs.)	2707
10.36	Turbocharger overpressure diagnosis (ERRM interface)	2712
10.37	Turbocharger plausibility diagnosis	2715
10.38	Turbocharger plausibility diagnosis (ERRM interface)	2740
10.39	Turbocharger plausibility diagnosis (Appl. Inc)	2743
10.40	Turbocharger control plausibility diagnosis (Appl. Inc.)	2747
10.41	Recirculation actuator plausibility diagnosis	2757
10.42	Recirculation actuator plausibility diagnosis (ERRM interface)	2774
10.43	Recirculation actuator plausibility diagnosis (Appl. Inc.)	2778
10.44	Turbocharger and pressure sensor EOL diagnosis	2784
10.45	Turbocharger overpressure diagnosis	2789
10.46	Turbocharger and pressure sensor EOL	2792
10.47	Turbocharger and pressure sensor EOL (Appl. Inc.)	2828


11 CUSF-Customer Supplied Functions 2832

11.1	System variables for customer specified functions	2833
11.2	Interface definitions of customer provided functionality	2844
11.3	Dynamic requirements of customer provided functionality	2941
11.4	Customer reference list	2976
11.5	Customer adaptation module: PWSL	2987
11.6	Customer adaptation module: IGSP	2990
11.7	Customer adaptation module: LACO	2992
11.8	Customer adaptation module: AIRT	3002
11.9	Customer adaptation module: DRRQ	3011
11.10	Customer adaptation module: EGCP	3014
11.11	Customer adaptation module: ENOS	3025
11.12	Customer adaptation module: ENSD	3031

11.13	Customer adaptation module: EVAC	3050
11.14	Customer adaptation module: INSY	3052
11.15	Customer adaptation module: KNCK	3066
11.16	Customer adaptation module: THRO	3074
11.17	Customer adaptation module: VVLI	3079
11.18	Customer adaptation module: VVTI	3081
11.19	Customer adaptation module: ENSC	3085
11.20	Customer adaptation module: INJR	3097
11.21	Customer adaptation module: ENSS	3111
11.22	Customer adaptation module: TRSM	3123
11.23	Customer adaptation module: ENSL	3147
11.24	Customer adaptation module: MISF	3153
11.25	Customer adaptation module: FUSL	3155
11.26	Customer adaptation module: FMSP	3165
11.27	Customer adaptation module: CBMD	3172
11.28	Customer adaptation module: CHRG	3177
11.29	Customer adaptation module: IGRE	3191
11.30	Customer adaptation module: EXT D	3193
11.31	Customer adaptation module: EGRC	3202
11.32	Customer adaptation module: HVAC	3206
11.33	Customer adaptation module: EXTC	3208
11.34	Customer adaptation module: LASP	3213
11.35	Customer adaptation module: ENLU	3215
11.36	Customer adaptation module: BRSY	3223
11.37	Customer adaptation module: RASL	3229
11.38	Customer adaptation module: VHSC	3258
11.39	Customer adaptation module: SYCF	3298
11.40	Customer adaptation module: NOXD	3312
11.41	Customer adaptation module: ECM2	3321
11.42	Customer adaptation module: INTC	3330
11.43	Customer adaptation module: FARM	3373

Released by	Schneider, Michaela	Date	2014-07-17	File	N/A
	Baseline	SCFN00Y0	Project	VW SIMOS 18.5 EA888 (SCF)	
	Document key	10265183 SPE 000 AE	Pages	Page 9 of 25091	
Regensburg ()		Copyright (C) Continental AG, 2007			A4: 2007-11

11.44	Customer adaptation module: CYTP	3375
11.45	Customer adaptation module: FUSP	3383
11.46	Customer adaptation module: INJP	3385
11.47	Customer adaptation module: VHSL	3387
11.48	Customer adaptation module: VHMD	3392
11.49	Customer adaptation module: ECOP	3398
11.50	Customer adaptation module: ESVS	3403
11.51	Customer adaptation module: DRVB	3409
11.52	Customer adaptation module: TQDR	3411
11.53	Customer adaptation module: TQLO	3415
11.54	Customer adaptation module: TQSP	3418
11.55	Customer adaptation module: ENTE	3431
11.56	Customer adaptation module: ERRM	3462
11.57	Customer adaptation module: EGPR	3463
11.58	Customer adaptation module: GEOL	3469
11.59	Customer adaptation module: VHST	3475
11.60	Customer adaptation module: EGRA	3479
11.61	Customer adaptation module: ALFU	3484
11.62	Customer adaptation module: PTQM	3486
11.63	Customer adaptation module: SCRMM	3504
11.64	Customer adaptation module: DRPD	3506
11.65	Customer adaptation module: CHRA	3515
11.66	Customer diagnostics interface (Appl. Inc.)	3527
11.67	CUSF Configuration data	3538
11.68	Customer adaptation module: NETM	3704
11.69	Customer adaptation module: PTOS	3706
11.70	Dynamic requirements of customer provided functionality (Appl. Inc.)	3711
11.71	Customer provided documentation	3728
11.72	Customer adaptation module: EGPA	3729
11.73	Brake servo unit pressure (CPF#115)	3734
11.74	Customer adaptation module: CLCC	3757

Released by	Schneider, Michaela	Date	2014-07-17	File	N/A
	Baseline	Project			
	SCFN00Y0	VW SIMOS 18.5 EA888 (SCF)			
	Document key	10265183 SPE 000 AE		Pages	Page 10 of 25091
Regensburg ()		Copyright (C) Continental AG, 2007			A4: 2007-11

11.75	Customer adaptation module: EMDA	3760
11.76	Customer adaptation module: EMSP	3763
11.77	Customer adaptation module: DGNC	3768
11.78	Customer adaptation module: CUSF	3775
11.79	Customer adaptation module: SECM	3846
11.80	Customer adaptation module: CEVC	3849

12 CUSF-SystemDefault 3851

12.1	BusErr-Module	3852
12.2	KD-Modul (Sum Errors)	3854
12.3	PDUErr-Modul	3864

13 DGNC-Diagnostic communication 3876

13.1	DGNC General	3877
13.2	MVB - Measured value blocks general	3882
13.3	MVB - Special blocks	3989
13.4	Application of ECU data via diagnosis tool	4010
13.5	UDS - Service interpreter (Appl.Inc.)	4012
13.6	UDS - SID 10h: diagnosticSessionControl Service	4017
13.7	UDS - SID 10h: diagnosticSessionControl Service (Appl. Inc.)	4020
13.8	UDS - SID 11h : ECUReset Service	4025
13.9	UDS - SID 11h : ECUReset Service (Appl. Inc.)	4027
13.10	UDS - SID 19h: readDTCInformation Service	4029
13.11	UDS - SID 19h: readDTCInformation Service (Appl. Inc.)	4032
13.12	UDS - SID 22h: readDataByIdentifier Service	4047
13.13	UDS - SID 22h: readDataByIdentifier Service (Appl. Inc.)	4050
13.14	UDS - SID 23h: readMemoryByAddress Service	4191
13.15	UDS - SID 23h: readMemoryByAddress Service (Appl. Inc.)	4196
13.16	UDS - SID 27h: securityAccess Service	4197
13.17	UDS - SID 27h: securityAccess Service (Appl. Inc.)	4204
13.18	UDS - SID 28h: communicationControl Service	4208

13.19	UDS - SID 28h: communicationControl Service (Appl. Inc.)	4211
13.20	UDS - SID 2Eh: writeDataByIdentifier Service	4217
13.21	UDS - SID 2Eh: writeDataByIdentifier Service (Appl. Inc.)	4219
13.22	UDS - SID 2Fh: inputOutputControlByIdentifier Service	4264
13.23	UDS - SID 2Fh: inputOutputControlByIdentifier Service (Appl. Inc.)	4268
13.24	UDS - SID 31h: routineControl Service	4272
13.25	UDS - SID 31h: routineControl Service (Appl. Inc.)	4275
13.26	UDS - SID 34h: requestDownload Service	4377
13.27	UDS - SID 36h: transferData Service	4383
13.28	UDS - SID 37h: requestTransferExit Service	4388
13.29	UDS - SID 3Eh: testerPresent Service	4391
13.30	UDS - SID 85h: controlDTCSetting Service	4393
13.31	UDS - SID 85h: controlDTCSetting Service (Appl. Inc.)	4395
13.32	UDS - SID 87h: LinkControl Service	4399
13.33	Annex	4403
13.34	UDS - Service interpreter (Only Boot SW)	4405

14	DRPD-Driver request pedals determination	4408
14.1	DRPD Configuration data	4409
14.2	AGGR adaptation: DRPD	4413
14.3	Pedal value sensor variables	4416
14.4	Pedal value sensor variables (Appl. Inc.)	4454
14.5	Kick down recognition /adaptation	4465
14.6	Brake switch variables	4491
14.7	Brake switch variables (Appl. Inc.)	4528
14.8	Driving mode selection via switch	4531
14.9	Kick down switch diagnosis	4577
14.10	Pedal value sensor diagnosis	4580
14.11	Brake switch diagnosis	4665
14.12	Driving mode selection via switch diagnosis	4723
14.13	Pedal value determination (gen)	4730

14.14	Pedal value sensor OBDI (gen)	4740
14.15	Brake switch OBDI (gen)	4751
15	DRRQ-Driver request	4752
15.1	AGGR adaptation: DRRQ	4753
15.2	Adaptive drive dynamics	4754
15.3	Pedal value interpretation	4775
15.4	Limp home for pedal value interpretation	4798
16	DRVB-Driveability	4810
16.1	DRVB Configuration data	4811
16.2	AGGR adaptation: DRVB	4812
16.3	Anti jerk parameters	4813
16.4	Anti jerk activation conditions	4825
16.5	Anti jerk controller	4832
16.6	Anti jerk (gen)	4839
17	ECM2-ECU Process Monitoring	4840
17.1	ECM2 General	4841
17.2	ECM2 Configuration data	4847
17.3	ECM2 Deviation Status of Customer Safety Functions	4851
17.4	Process monitoring	4868
17.5	Interfaces for process monitoring	4891
17.6	Debounce mechanism	4933
17.7	Configuration of process monitoring (Appl. Inc.)	4940
17.8	Monitoring of A/D conversion	4958
17.9	Monitoring of coolant temperature	4966
17.10	Monitoring of idle speed controller (Appl. Inc.)	4970
17.11	Monitoring of idle speed controller	4990
17.12	Monitoring of torque losses (Appl. Inc.)	4995
17.13	Monitoring of torque losses	5007

17.14	Monitoring of engine speed	5014
17.15	Monitoring of pedal value signal (Appl. Inc.)	5020
17.16	Monitoring of pedal value signal	5049
17.17	Monitoring of mass fuel flow signal	5101
17.18	Required mass fuel flow	5108
17.19	Monitoring of cruise control conditions	5113
17.20	Desired indicated engine torque (Appl. Inc.)	5160
17.21	Actual fuel mass flow	5185
17.22	Actual indicated engine torque (Appl. Inc.)	5215
17.23	Actual indicated engine torque	5222
17.24	Monitoring of engine speed limitation	5229
17.25	Processor monitoring by copy of process monitoring	5234
17.26	Fault reaction of process monitoring	5273
17.27	Error memory management of process monitoring	5291
17.28	Error memory management of process monitoring (Appl. Inc.)	5321
17.29	Monitoring of safety relevant ECU outputs	5363
17.30	Communication monitoring of cruise control unit	5429
17.31	Communication monitoring of electronic ignition lock unit	5472
17.32	Communication monitoring of traction control unit	5481
17.33	Communication monitoring of transmission unit	5579
17.34	Communication monitoring of electrical machine control unit	5618
17.35	Communication monitoring	5643
17.36	Monitoring function for clutch 0 state	5684
17.37	Monitoring of vehicle torque coordination	5699
17.38	Monitoring of driver demand acceleration	5702
17.39	Monitoring of driver demand brake	5712
17.40	Monitoring of driver demand coordination	5718
17.41	Monitoring of driver demand drag	5732
17.42	MonDrvModSwt	5739
17.43	Monitoring function for Elm interface, actual values	5747
17.44	Monitoring of electric machine setpoint	5758